

## PROMO5326 Control unit for demo flightcases

## Product information:

To power and control the demo flightcases, PROMO5321, PROMO5322 and PROMO5323 showcased on this website, we used the following setup:

- 1 x FC104 19" flightcase 4HE 507mm depth
- 1 x COM108 Compact public address amplifier
  - 1 x MBS310 Rack mounting set for COM108
- 1 x XMP44 Professional modular audio system
- 1 x BMP40 SourceCon™ bluetooth module
- 1 x ARU204 4 Channel digital relay unit with RS485 and TCP/IP
- 1 x ARU208 8 Channel digital relay unit with RS485 and TCP/IP  $\,$ 
  - 1 x CASY001 CASY chassis 12 space
    - 2 x CASY101 CASY 1 space closed blind plate
    - 1 x CASY103 CASY 1 space with 1 x D-size hole
    - 2 x CASY108 CASY 1 space with 1 x TRUE1 hole
- 1 x CASY122 CASY 1 space with XLR male to 3-pin terminal block
- $1 \times CASY126$  CASY 1 space with  $2 \times XLR$  male to 3-pin terminal block
- $2 \times CASY142$  CASY 1 space with  $2 \times Male$  SpeakON to 4-pin terminal block
  - 1 x CASY301 CASY 3 space closed blind plate
  - 2 x NAC3FPX-TOP PowerCON TRUE1 16A power-out
  - 1 x NAC3MPX-TOP PowerCON TRUE1 16A power-in
  - 1 x PSR109GS 19" power distribution unit
  - 1 x Standard WiFi switch

To keep the products protected during traveling the total power and control setup is kept in a FC104.

Keep in mind, this control unit is a recommended configuration all 3 units but can be adapted to your own needs. The control unit can be configured to your own needs by ordering the goods separately. It is also not possible to provide you with a standard cabling or product scheme. However, our technical department is always available to advise you!



## **Product Features:**

Dimensions	20.83 x 8.27 x 27.047 " (W x H x D) (excl. rubber feet)
Unit height	4 HE
Max. usable depth	19.016 "
Construction	0.35 " high-quality plywood
Finish	ProShield™ top layer
Handles	2 x Medium heavy-duty (Penn Elcom H7154Z)
Latches	4 x Medium MOL™ (Penn Elcom L907/928/10)

AUDAC - PROMO5326 - 21/11/2025 20:44 UTC