

Highlights:

- Warm & true to nature sound
- Weatherproof - IP55 rating
- Countless mounting possibilities
- Diverse connections possibilities
- High grade aluminum construction
- 70V/100V transformer option available

Product information:

"A sound that lasts"

The VIRO is a powerful 2-way performance speaker which is designed for outdoor and indoor use, ensuring true-to-nature, high fidelity reproduction of music and speech in every environment, ranging from residential applications to the most demanding outdoor applications in parks, hotels and even clubs.

Crafted in high-grade aluminium with incredible attention to detail. The material choice goes well beyond aesthetics. It also provides superior acoustic properties thanks to its material stiffness and seamless surfaces that eliminate any distortion of your sound.

The aluminium construction and grill with hydrophobic cloth provides the necessary protection for all weather conditions. The combination of the cloth, sealing rubbers and drainage holes on the bottom of the speaker make it IP55 compliant (Successfully endured 720h salt spray test).

Exchange your connections easily. From cable glands with rubber grommets to optional SpeakON connections and even an optional 70/100V transformer (TRV106).

Applications:

- Bars & Restaurants
- Clubs



Certification:

 IP55

Properties:

 Weatherproof

Impedance:

Ω 8 Ohm Ω 16 Ohm

Voltage:

 70-100 Volt

System specifications:

Speaker type	Compact performance 2-way coaxial	
Peak power handling	240 W	
Program power handling	120 W	
RMS/AES power handling	60 W	
Impedance	8 Ω (VIRO5)	
	16 Ω (VIRO5D)	
Sensitivity (1W/1m)	89 dB	
Sound Pressure (Max. W/1m)	110 dB	
Frequency	Range (-10 dB)	50 Hz - 20 kHz
Dispersion	Conical	160° (average 500 Hz to 5 kHz @ -6 dB)
Drivers	HF	Soft dome treated silk 1"
	LF	5 1/4" Treated paper
Connectors	4-pin Euro Terminal Block	
Ingress Protection rating	IP55	
Outdoor resistance	720 hrs salt spray test	

Product Features:

Dimensions		7.80 x 9.25 x 7.52 " (W x H x D) (Incl. bracket)
		7.087 x 7.087 x 7.52 " (W x H x D) (Excl. bracket)
Mounting	Mounting pattern	40 x 70 mm mounting pattern (e.g. pole or ground pin fitting)
Mounting & handling	Stand fitting	3/8" stand fitting (microphone stand)
Construction		Textured powder coated aluminium 4 mm
Front finish		Aluminium grill with hydrophobic cloth
Colours		White (RAL9003) (VIRO5/W & VIRO5D/W)
		Black (RAL9005) (VIRO5/B & VIRO5D/B)
Weight		9.26 lb
Accessories	Included	Mounting bracket
		Connection plate with 2 x M16 cable gland
		Connection plate with cable grommit
	Optional	TRV106 70-100V transformer module
		CVS102 SpeakON connection plate
		MBK523/G Ground pin
		MBK530 Pole mount
		STG601 Steel drop safety wire (gripple)
		MBK465 Table stand

Variants:

- VIRO5/B - Black version - 8Ω
- VIRO5/W - White version - 8Ω
- VIRO5D/B - Black version - 16Ω
- VIRO5D/W - White version - 16Ω